This powerful Nilfisk easily handles larger and frequent cleaning tasks. From gentle cleaning of more soft or sensitive surfaces to blasting away ingrained dirt.

It has a long-lasting induction motor and offers a large range of operation with its 10m steel armed hose.

It is equiped with many invaluable features, when you need to work for longer periods of time; telescopic handle, sturdy wheels, long hose and one-hand operated hose reel as well as a rubber suspension to ensure lower noise.

To increase performance, this Nilfisk comes with Click&Clean connectivity for a range of optional accessories.

- 150 bar, max pressure.
- Sturdy built with alluminum pump and long-life induction motor.
- Automatic start/ stop system.
- 10m reinforced steelarmed hose for wider coverage and long life or 9m soft hose
- One-hand operated hose reel
- Telescopic handle with sturdy and robust aluminum tubes.
- Rubber suspension ensures a lower noise when working
- Easy storage of gun, lance, nozzles and foam sprayer onboard.
- Convenient storage of electric cable.
- Click&Clean nozzle system ensures quick and easy change of nozzle.
- The X-TRA model features a built-in trolley for increased mobility.
- Can be used as a stationary machine with optional wall hook.

#### Standard equipment

	·	1				1
	Included accessories	Ref. no.	Min. required	E 150.2-10 H X-TRA UK	E 150.2-10 H X-TRA EU	E 150.2-10 PH X-TRA EU
Hose and Co	nnection					
	HOSE STEEL ARMED 10M FOR MODEL	128500656	0	•	•	•
9	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0			
Nozzle - High	Pressure Washer					
4	POWER SPEED NOZZLE	128501153	0	•	•	•
	PR TORNADO RED2 LINES CLICK	128500657	0	•	•	•
Accessory						
	CLEANING TOOL BLACK	6520844	0	•	•	•







Picture shown may not represent model quoted

#### Pressure washers

#### The powerful, long-life, high-pressure washer. With long hose range for larger cleaning tasks

	Included accessories		Min. required	E 150.2-10 H X-TRA UK	E 150.2-10 H X-TRA EU	E 150.2-10 PH X-TRA EU
T	FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
	G4 NOZZLE TUBE SHORT	128500676	0	•	•	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•	•	•
<b>b</b>	Patio Cleaner	128500702	0			•

Standard equipment

	Included accessories	Ref. no.	Min. required	E 150.2-9 X- TRA EU	E 150.2-9 P X- TRA EU
Hose and Cor	nnection				
	HOSE STEEL ARMED 10M FOR MODEL	128500656	0		
9	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0	•	•
Nozzle - High	Pressure Washer				
Ą	POWER SPEED NOZZLE	128501153	0	•	•
	PR TORNADO RED2 LINES CLICK	128500657	0	•	•
Accessory		1			
	CLEANING TOOL BLACK	6520844	0	•	•
T	FOAMSPRAYER WITH BOTTLE	128500077	0	•	•
	G4 NOZZLE TUBE SHORT	128500676	0	•	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•	•



	Included accessories		Ref. no.	Min. required	E 150.2-9 X- TRA EU	E 150.2-9 P X- TRA EU
•	Patio Cleaner		128500702	0		•
Model		E 15	0.2-10 H X-TRA UK	E 150.2-10 E		150.2-10 PH X- TRA EU
Ref. no.			128471201	12847	71200	128471202
PRODUCT F	EATURES					
Trolley			•	•	•	•
Aluminium pu	ump		•	•		•
Lance and sp	oray gun storage		•	•		•
Storage of ac	ccessories		•	•	•	•
Cable storage	e		•	•	•	•
Click&Clean	(C&C) nozzle concept		•	•	•	•
Gun with quid	ck connection and swivel		•	•	•	•
Superflex (ste	eel armed) hose		•	•	•	•
Automatic sta	art/stop		•	•	•	•
Soft grip			•	•	•	•
Telescopic ha	andle		•	•	•	•
Wireless Pow	verGrip					
Pressure reg	ulation in nozzle		•		•	•
Model				E 150.2- E		150.2-9 P X-TRA EU
Ref. no.				12847	70766	128470767
PRODUCT F	EATURES					
Trolley				•	•	•
Aluminium pu	ump			•	•	•
Lance and sp	pray gun storage			•	•	•
Storage of ac	ccessories			•	•	•
Cable storage	e				•	•
Click&Clean	(C&C) nozzle concept				•	•
Gun with quid	ck connection and swivel				•	•
Superflex (ste	eel armed) hose					
Automatic sta	art/stop				•	•
Soft grip					•	•
Telescopic ha	andle				•	•
Wireless Pow	verGrip					



Ref. no.128470760128470760PRODUCT FEATURESPressure regulation in nozzle-Technical specificationsE 150.2-10 H.X:RAE 150.2-10 H.X:RAE 150.2-10 H.X:RAPump pressure (bar/MPa)Max 150/ max 15Max 150/ max 15Max 150/ max 15Rated power (kW)2.12.12.12.1Voltage/phase/frequency/current (V/-/Hz/A)250 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 (1-7 / 50 / 20 - 240 / 1-7 / 50 / 20 / 20 / 20 / 20 / 20 / 20 / 20	Model		E 150.2-9 X-TRA EU	E 150.2-9 P X-TRA EU
Pressure regulation in nozzle     •       Technical specifications     E 150.2-10 H X-TR     E 150.2-10 H X-TR     E 150.2-10 H X-TR       Pump pressure (bar/MPa)     Max 150/ max 15     Max 150/ max 15     Max 150/ max 15       Rated power (kW)     2.1     2.1     2.1       Voltage/phase/frequency/current (V/-/Hz/A)     230-240 / 1- / 50 / 10     230-240 / 1- / 50 / 10       Water flow Qmax/Qiec (I/h)     500/ 400     500/ 400     500/ 400       Cable length (m)     5     5     5       Hose length (m)     10     10     10       Max. inlet temperature (°C)     40     40     40       Length x width x height (cm)     39.5 x 34.5 x 87.5     39.5 x 34.5 x 87.5     39.5 x 34.5 x 87.5       Veight (kg)     19.8     19.8     19.8     19.8       Pump pressure (bar/MPa)     Kart 50/ max 15     Kart 50/ max 15     Kart 50/ max 15       Voltage/phase/frequency/current (V/-/Hz/A)     19.8     19.8     19.8       Pump pressure (bar/MPa)     Kart 50/ max 15     Kart 50/ max 15     12.1       Voltage/phase/frequency/current (V/-/Hz/A)     230 - 240 / 1- / 50 / 10	Ref. no.		128470766	128470767
Technical specifications     E 150.2-10 H X-TRA     E	PRODUCT FEATURES			
Technical specifications     UK     EU     TRA EU       Pump pressure (bar/MPa)     Max 150/ max 15     Max 150/ max 15     Max 150/ max 15       Rated power (kW)     2.1     2.1     2.1     2.0       Voltage/phase/frequency/current (V/~/Hz/A)     230 - 240/ 1~/ 50/     230 - 240/ 1~/ 50/     10       Water flow Qmax/Qiec (l/h)     500/ 400     500/ 400     500/ 400     500/ 400       Cable length (m)     5     5     5     5       Hose length (m)     10     10     10     10       Max. inlet temperature (°C)     40     40     40     40       Length x width x height (cm)     39.5 x 34.5 x 87.5     39.5 x 34.5 x 87.5 <td>Pressure regulation in nozzle</td> <td></td> <td>•</td> <td>•</td>	Pressure regulation in nozzle		•	•
Rated power (kW)     2.1     2.1     2.1       Voltage/phase/frequency/current (V/~/Hz/A)     230 - 240 / 1 - / 50 / 10     230 - 240 / 1 - / 50 / 10     230 - 240 / 1 - / 50 / 10     230 - 240 / 1 - / 50 / 10     10       Water flow Qmax/Qiec (I/h)     500/ 400     500/ 400     500/ 400     500 / 400     500 / 400     230 - 240 / 1 - / 50 / 10     <	Technical specifications			
Voltage/phase/frequency/current (V/~/Hz/A)     230 - 240 / 1 - / 50 / 10     230 - 240 / 1 - / 50 / 10     230 - 240 / 1 - / 50 / 10       Water flow Qmax/Qiec (I/h)     500 / 400     500 / 400     500 / 400     500 / 400       Cable length (m)     5     5     5     5       Hose length (m)     10     10     10     10       Max. inlet temperature (°C)     40     40     40       Length x width x height (cm)     39.5 x 34.5 x 87.5     39.5 x 34.5 x 87.5     39.5 x 34.5 x 87.5       Weight (kg)     19.8     19.8     19.8     19.8       Technical specifications     E 150.2 - 9 X - TRA EU     E 150.2 - 9 X - TRA EU     210 - 240 / 1 - / 50 / 10       Pump pressure (bar/MPa)     Max 150/ max 15     Max 150/ max 15     Max 150/ max 15       Rated power (kW)     2.1     2.1     2.1     210 - 240 / 1 - / 50 / 10       Voltage/phase/frequency/current (V/~/Hz/A)     500 / 400     500 / 400     500 / 400       Cable length (m)     9     9     9     9       Max. inlet temperature (°C)     40     40     40       Length x width x height (cm)	Pump pressure (bar/MPa)	Max 150/ max 15	Max 150/ max 15	Max 150/ max 15
Voitage/phase/frequency/current (V/~/H2/A)     10     10     10     10       Water flow Qmax/Qiec (I/h)     500/ 400     500/ 400     500/ 400     500/ 400       Cable length (m)     5     5     5       Hose length (m)     10     10     10       Max. inlet temperature (*C)     40     40     40       Length x width x height (cm)     39.5 x 34.5 x 87.5     39.5 x 34.5 x 87.5     39.5 x 34.5 x 87.5       Weight (kg)     19.8     19.8     19.8       Technical specifications     E 150 2-9 X-TRA EU     E 150 2-9 P X-TRA EU       Pump pressure (bar/MPa)     Max 150/ max 15     Max 150/ max 15       Rated power (kW)     2.1     2.1     2.1       Voltage/phase/frequency/current (V/~/Hz/A)     230 - 240 / 1~ / 50 / 10     10     10       Water flow Qmax/Qiec (l/h)     500/ 400     500/ 400     500/ 400     500/ 400       Cable length (m)     5     5     5     5       Hose length (m)     9     9     9     9       Max. inlet temperature (°C)     40     40     40	Rated power (kW)	2.1	2.1	2.1
Cable length (m)   5   5     Hose length (m)   10   10   10     Max. inlet temperature (°C)   40   40   40     Length x width x height (cm)   39.5 x 34.5 x 87.5     Weight (kg)   19.8   19.8   19.8   19.8     Technical specifications   E 150.2-9 X-TRA   E 150.2-9 X-TRA   E 150.2-9 X-TRA     Pump pressure (bar/MPa)   Max 150/ max 15   Max 150/ max 15     Rated power (kW)   2.1   2.1     Voltage/phase/frequency/current (V/~/Hz/A)   230-240/1-/50/10   10     Water flow Qmax/Qiec (l/h)   5   5     Hose length (m)   9   9     Max. inlet temperature (°C)   40   40     Length x width x height (cm)   39.5 x 34.5 x 87.5   39.5 x 34.5 x 87.5	Voltage/phase/frequency/current (V/~/Hz/A)			
Hose length (m)   10   10   10     Max. inlet temperature (°C)   40   40   40     Length x width x height (cm)   39.5 x 34.5 x 87.5   39.5 x 34.5 x 87.5   39.5 x 34.5 x 87.5     Weight (kg)   19.8   19.8   19.8     Technical specifications   E 150.2-9 X-TRA   E 150.2-9 X-TRA   E 150.2-9 X-TRA     Pump pressure (bar/MPa)   Max 150/ max 15   Max 150/ max 15     Rated power (kW)   2.1   2.1     Voltage/phase/frequency/current (V/~/Hz/A)   200 - 240 / 1 - / 50 / 10   30 - 240 / 1 - / 50 / 10     Water flow Qmax/Qiec (l/h)   500 / 400   500 / 400   500 / 400     Cable length (m)   9   9   9     Max. inlet temperature (°C)   40   40   40     Length x width x height (cm)   39.5 x 34.5 x 87.5   39.5 x 34.5 x 87.5	Water flow Qmax/Qiec (l/h)	500/ 400	500/ 400	500/ 400
Max. inlet temperature (°C)404040Length x width x height (cm)39.5 x 34.5 x 87.539.5 x 34.5 x 87.539.5 x 34.5 x 87.5Weight (kg)19.819.819.819.8Technical specificationsE 150.2-9 X.TRAE 150.2-9 D.X.TRAPump pressure (bar/MPa)Max 150/ max 15Max 150/ max 15Rated power (kW)2.12.12.1Voltage/phase/frequency/current (V/~/Hz/A)S00/ 400500/ 400Cable length (m)999Max. inlet temperature (°C)404040Length x width x height (cm)39.5 x 34.5 x 87.539.5 x 34.5 x 87.5	Cable length (m)	5	5	5
Length x width x height (cm)   39.5 x 34.5 x 87.5   39.5 x 34.5 x 87.5   39.5 x 34.5 x 87.5     Weight (kg)   19.8   19.8   19.8     Technical specifications   E 150.2-9 X-TRA   E 150.2-9 X-TRA     Pump pressure (bar/MPa)   Max 150/ max 15   Max 150/ max 15     Rated power (kW)   2.1   2.1     Voltage/phase/frequency/current (V/~/Hz/A)   200 - 240 / 1~ / 50 / 10   300 - 240 / 10     Water flow Qmax/Qice (I/h)   500/ 400   500 / 400     Cable length (m)   9   9     Max. inlet temperature (°C)   40   40     Length x width x height (cm)   39.5 x 34.5 x 87.5   39.5 x 34.5 x 87.5	Hose length (m)	10	10	10
Weight (kg)     19.8     19.8     19.8       Technical specifications     E 150.2-9 X-TRA EU     E 150.2-9 P.X-TRA EU     E 150.2-9 P.X-TRA EU     E 150.2-9 P.X-TRA EU     E 150.2-9 P.X-TRA EU     Max 150/max 15       Pump pressure (bar/MPa)     Max 150/max 15     Max 150/max 15     Max 150/max 15       Rated power (kW)     2.1     2.1     2.1       Voltage/phase/frequency/current (V/~/Hz/A)     230-240 / 1~/50 / 10     230-240 / 1~/50 / 10     10       Water flow Qmax/Qiec (l/h)     500/ 400     500/ 400     500/ 400     500/ 400       Cable length (m)     5     5     5     5       Hose length (m)     9     9     9     9       Max. inlet temperature (°C)     40     40     40       Length x width x height (cm)     39.5 x 34.5 x 87.5     39.5 x 34.5 x 87.5	Max. inlet temperature (°C)	40	40	40
Technical specificationsE 150.2-9 X-TRA EUE 150.2-9 P X-TRA EUPump pressure (bar/MPa)Max 150/ max 15Rated power (kW)2.12.1Voltage/phase/frequency/current (V/~/Hz/A)230 - 240 / 1~ / 50 / 10230 - 240 / 1~ / 50 / 10Water flow Qmax/Qiec (l/h)500/ 400500/ 400Cable length (m)55Hose length (m)99Max. inlet temperature (°C)4040Length x width x height (cm)39.5 x 34.5 x 87.539.5 x 34.5 x 87.5	Length x width x height (cm)	39.5 x 34.5 x 87.5	39.5 x 34.5 x 87.5	39.5 x 34.5 x 87.5
Fechnical specificationsEUEUPump pressure (bar/MPa)Max 150/ max 15Max 150/ max 15Rated power (kW)2.12.1Voltage/phase/frequency/current (V/~/Hz/A)230 - 240 / 1~ / 50 / 10230 - 240 / 1~ / 50 / 10Water flow Qmax/Qiec (l/h)500/ 400500/ 400Cable length (m)55Hose length (m)99Max. inlet temperature (°C)4040Length x width x height (cm)39.5 x 34.5 x 87.539.5 x 34.5 x 87.5	Weight (kg)	19.8	19.8	19.8
Rated power (kW)   2.1   2.1     Voltage/phase/frequency/current (V/~/Hz/A)   230 - 240 / 1~ / 50 / 10   230 - 240 / 1~ / 50 / 10     Water flow Qmax/Qiec (I/h)   500 / 400   500 / 400     Cable length (m)   5   5     Hose length (m)   9   9     Max. inlet temperature (°C)   40   40     Length x width x height (cm)   39.5 x 34.5 x 87.5   39.5 x 34.5 x 87.5	Technical specifications			
Voltage/phase/frequency/current (V/~/Hz/A)   230 - 240 / 1~ / 50 / 10     Water flow Qmax/Qiec (I/h)   500 / 400     Cable length (m)   5   5     Hose length (m)   9   9     Max. inlet temperature (°C)   40   40     Length x width x height (cm)   39.5 x 34.5 x 87.5   39.5 x 34.5 x 87.5	Pump pressure (bar/MPa)		Max 150/ max 15	Max 150/ max 15
Voitage/phase/frequency/current (V/~/Hz/A)     10     10       Water flow Qmax/Qiec (I/h)     500/ 400     500/ 400       Cable length (m)     5     5       Hose length (m)     9     9       Max. inlet temperature (°C)     40     40       Length x width x height (cm)     39.5 x 34.5 x 87.5     39.5 x 34.5 x 87.5	Rated power (kW)		2.1	2.1
Cable length (m)   5   5     Hose length (m)   9   9     Max. inlet temperature (°C)   40   40     Length x width x height (cm)   39.5 x 34.5 x 87.5   39.5 x 34.5 x 87.5	Voltage/phase/frequency/current (V/~/Hz/A)			
Hose length (m)     9     9       Max. inlet temperature (°C)     40     40       Length x width x height (cm)     39.5 x 34.5 x 87.5     39.5 x 34.5 x 87.5	Water flow Qmax/Qiec (l/h)		500/ 400	500/ 400
Max. inlet temperature (°C) 40   Length x width x height (cm) 39.5 x 34.5 x 87.5	Cable length (m)		5	5
Length x width x height (cm) 39.5 x 34.5 x 87.5 39.5 x 34.5 x 87.5	Hose length (m)		9	9
	Max. inlet temperature (°C)		40	40
Weight (kg) 19.8 19.8	Length x width x height (cm)		39.5 x 34.5 x 87.5	39.5 x 34.5 x 87.5
	Weight (kg)		19.8	19.8

ullet Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

	Accessories	Ref. no.	Min. required	E 150.2-10 H X-TRA UK	E 150.2-10 H X-TRA EU	E 150.2-10 PH X-TRA EU
Brush						
	Auto brush	6411131	0	0	0	0
0	Car brush head	128500463	0	0	0	0



	Accessories	Ref. no.	Min. required	E 150.2-10 H X-TRA UK	E 150.2-10 H X-TRA EU	E 150.2-10 PH X-TRA EU
	FIXED BRUSH SHORT NILFISK SP	128500685	0	0	0	0
	Garden brush head	128470457	0	0	0	0
	RIM BRUSH HEAD	128470458	0	0	0	0
	ROTARY BRUSH	6410762	0	0	0	0
	ROTARY BRUSH	126411395	0	0	0	0
Accessory				1	1	
$\bigcirc$	15M DRAIN&TUBE CLEANER	6410766	0	0	0	0
	CLEANING TOOL BLACK	6520844	0	●	•	•
-	DRAIN AND TUBE 8M	128500461	0	0	0	0
T	FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
	G4 NOZZLE TUBE SHORT	128500676	0	•	•	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•	•	•
	INLET SUCTION HOSE 3M	128500673	0	0	0	0



	Accessories	Ref. no.	Min. required	E 150.2-10 H X-TRA UK	E 150.2-10 H X-TRA EU	E 150.2-10 PH X-TRA EU
	MULTI BRUSH	128470456	0	0	0	0
	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	O	0	0
	NILFISK POWER PATIO	128500955	0	0	0	0
	NILFISK WATER FILTER	128500674	0	0	0	0
•	Patio Cleaner	128500702	0	0	0	•
d	ROOF CLEANER	128470040	0	0	0	O
]	Under Chassis Spray Lance	6410763	0	0	0	0
	VSB SET - GREEN	6410891	0	0	0	0
J.	WALL HOOK	106411386	0	0	0	0
6	Water Emptying Kit	126411387	0	0	0	0
Nozzle - High	Pressure Washer					
4	POWER SPEED NOZZLE	128501153	0	•	•	•
	PR TORNADO RED2 LINES CLICK	128500657	0	•	•	•



	Accessories	Ref. no.	Min. required	E 150.2-10 H X-TRA UK	E 150.2-10 H X-TRA EU	E 150.2-10 PH X-TRA EU
4	Under Chassis Nozzle	6411135	0	0	0	0
	Wide Angled Auto & Cycle Nozzle	6411136	0	0	0	0
Hose and Co	nnection					
	HOSE STEEL ARMED 10M FOR MODEL	128500656	0	•	•	•
9	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0			
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0	0
Accessory Kit						
	MULTI BRUSH KIT	128470459	0	0	0	0
00 <b>0</b> 0	O-RING KIT CONSUMER HPW	128500292	0	0	0	0

ullet Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

	Accessories	Ref. no.	Min. required	E 150.2-9 X- TRA EU	E 150.2-9 P X- TRA EU
Brush					
	Auto brush	6411131	0	0	0
0	Car brush head	128500463	0	0	0
	FIXED BRUSH SHORT NILFISK SP	128500685	0	0	0
	Garden brush head	128470457	0	0	0



	Accessories	Ref. no.	Min. required	E 150.2-9 X- TRA EU	E 150.2-9 P X- TRA EU
	RIM BRUSH HEAD	128470458	0	0	0
	ROTARY BRUSH	6410762	0	0	0
	ROTARY BRUSH	126411395	0	0	0
Accessory					
0	15M DRAIN&TUBE CLEANER	6410766	0	0	0
	CLEANING TOOL BLACK	6520844	0	•	•
<u> </u>	DRAIN AND TUBE 8M	128500461	0	o	0
T	FOAMSPRAYER WITH BOTTLE	128500077	0	•	•
	G4 NOZZLE TUBE SHORT	128500676	0	•	•
	G4 SPRAY HANDLE W.SOFT COATING	128500071	0	•	•
	INLET SUCTION HOSE 3M	128500673	0	o	0
	MULTI BRUSH	128470456	0	0	0
	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	o	0



	Accessories	Ref. no.	Min. required	E 150.2-9 X- TRA EU	E 150.2-9 P X- TRA EU
	NILFISK POWER PATIO	128500955	0	0	0
	NILFISK WATER FILTER	128500674	0	0	0
•	Patio Cleaner	128500702	0	0	•
4	ROOF CLEANER	128470040	0	0	0
)	Under Chassis Spray Lance	6410763	0	0	0
	VSB SET - GREEN	6410891	0	0	0
	WALL HOOK	106411386	0	0	0
<b>°</b>	Water Emptying Kit	126411387	0	0	0
Nozzle - High	Pressure Washer				
Ą	POWER SPEED NOZZLE	128501153	0	•	•
	PR TORNADO RED2 LINES CLICK	128500657	0	•	•
4	Under Chassis Nozzle	6411135	0	0	0
Ą	Wide Angled Auto & Cycle Nozzle	6411136	0	0	0



Accessories		Ref. no.	Min. required	E 150.2-9 X- TRA EU	E 150.2-9 P X- TRA EU
Hose and Connection					
	HOSE STEEL ARMED 10M FOR MODEL	128500656	0		
9	HOSE TEXTILE SOFT 9M FOR MODEL	128500654	0	•	•
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0
Accessory Kit					
	MULTI BRUSH KIT	128470459	0	0	o
00 <b>0</b> 0	O-RING KIT CONSUMER HPW	128500292	0	0	0

