Nilfisk Attix Vacuum Cleaner Range

Leading class of versatile and robust industrial wet and dry vacuum cleaners



Specifications	Attix 30-01 PC	Attix 40-01 PC INOX	Attix 50-01 PC
Airflow - Itr/min - Itr/sec	3700 - 61.67	3700 - 61.67	3700 - 61.67
Vacuum - mbar	250	250	250
Voltage - V/~/Hz	220/1/50	220/1/50	220/1/50
Electric motor - W (PIEC)	1200	1200	1200
Motor rating - W (PMAX)	1500	1500	1500
Capacity of container - Itr	30	37	47
Working noise level - dB(A)	59	59	59
Length of suction hose - m	3	3	3
Length X width X height - mm	450 x 380 x 595	450 x 440 x 735	450 x 380 x 750
Weight - Kg	10	13	11

This class leading machine offers a highly effective solution to a multitude of vacuum cleaning, dust extraction, spillage removal and material loading applications throughout all sectors of industry and commerce.

Fine or coarse substances, such as dust, gravel, shavings or non-flammable liquids present no problems to the ingenious filter system, which ensures constantly high suction performance through a reverse air pulse based cleaning method.





www.industroclean.co.za

info@industroclean.co.za



Nilfisk Attix Vacuum Cleaner Range

The Attix 30-01 PC, Attix 40-01 PC Inox and Attix 50-01 PC features:

- A comprehensive set of multipurpose cleaning attachments.
- Provides class leading performance in terms of air flow, vacuum and versatility;
- Built from high quality materials to ensure a trouble fee and long service life; features faultless
 ergonomics based on our decades of experience in building vacuumation equipment and our on-gong
 efforts to perfect our product.
- Soft Start facility to minimize start-up power demand, thereby protecting and substantially extending the vacuum motors service life expectancy; (Attix 50-01 PC)

Standard accessories:

- Curved steel handle:
- Chromed steel extension tubes, 2-part;
- Ground attachment, working width 360 mm;
- Crevice nozzle:
- Disposable fleece filter bag;
- PET filter cartridge, washable.
- Flexible suction hose, with a rotating coupling at the container end and a quick connect coupler at the attachment end; length 3 m, 0 36 mm.

Key features:

- High performance "By-pass" type vacuum motor with separate cooling system and permanently sealed bearings.
- Long life, washable PET filter cartridge, concertina design with more than 3150 cm2 filtration area.
- Push and clean filter cleaning system to ensure constantly high suction performance, critical for applications involving the picking up of very fine substances.
- Extremely low operating noise level for non-intrusive vacuuming operation.
- Large capacity, disposable fleece filter bag.
- Two rear mounted fixed wheels, as well as two front mounted heavy duty castor wheels, for optimum stability and easy maneuverability.
- Sturdy Polyethylene dirt receptacle, non corrosive, impact resistant (Attix 30 and 50).
- High grade stainless steel receptacle (Attix 40-01 PC)





www.industroclean.co.za

info@industroclean.co.za

