# indusolve

#### **HEAVY DUTY CLEANER**



#### **Uses**

For the removal of oil, grease and other heavy duty soiling on walls, floors, doors etc.

## **Application**

By hand, in wet mopping equipment, single disc machine diluted with cold or warm water. In case of heavy soiling, leave cleaning solution to soak for approximately 10 minutes, then rinse.

#### **Dilution**

Maintenance cleaning: 50-100ml:10lt water

Periodic cleaning: 200-500ml:10lt water

# **Supplies**

5lt container – 01662

20lt container - 01660

### **Compounds**

- <5% non-ionic surfactants</p>
- Solvent
- Silicates

#### **Hazardous components**

None

#### Note

Not suitable for the maintenance cleaning of floor coverings treated with self-shine dispersions, as well as for wooden, asphalt, natural rubber and pained coverings. On linoleum, use only up to 500ml:10lt water.

## **Storage**

Protect from sunlight and do not expose to temperatures exceeding 50°C.

## **Technical specifications**

Description	Result
Colour	Clear
pH in concentrate	12.5 ± 0.5
Specific gravity at 20°C	1.050 g/ml

Specifications and details are subject to change without prior notice

Industroclean (Pty) Ltd Tel: +27 11 801 4600

Mail: info@industroclean.co.za www.industroclean.co.za