# prosolve mk

#### **HEAVY DUTY CLEANER**



#### Uses

For the removal of heavy duty soiling on surfaces.

#### **Application**

Can be used with single disc machines, wet mopping, or by hand application using a bucket and cleaning cloth, pad or sponge. In case of heavy soiling, leave solution to soak for approximately 10 minutes, then rinse.

#### **Dilution**

Maintenance cleaning: 100ml

## **Supplies**

100ml (10) - P02227

50ml (10) - P02232

#### **Storage**

Protect from sunlight and do not expose to temperatures exceeding 50°C.

## **Compounds**

- <4% non-ionic surfactants</p>
- <2% anionic surfactants

## **Hazardous components**

- <5% 2-Butyoxyethanol</li>
- <3% Ethanolamine</p>

#### **Note**

Not suitable for the maintenance cleaning of floor coverings treated with self-shine dispersions, as well as wooden, asphalt, natural rubber and painted coverings. On linoleum use only up to 500ml:10lt water. Not suitable for automatic scrubber-driers.

#### **Technical specifications**

Description	Result
Colour	Orange
pH in concentrate	13.0 ± 0.5
Specific gravity at 20°C	1.060 g/ml

Specifications and details are subject to change without prior notice

Industroclean (Pty) Ltd Tel: +27 11 801 4600

Mail: info@industroclean.co.za www.industroclean.co.za

IS0085