



## Fatigue-Step

### Safety rubber tiles for playgrounds and the workplace



- Interlocking rubber floor tile system to cover large or small areas.
- Offers you safety for playgrounds.
- Anti-slip surface reduces risks (tested to DIN 51130).
- Ideal safety matting for outdoor areas.
- Durable and easy to clean.
- Easy to relocate or replace.
- Fits in natural environment.
- Suitable for all weather, extreme temperatures and resists wind uplift
- Open holes allow grass growth and provide optimal drainage.

## Parts

Part Number	Size	Colour	Weight (kg)
SS010001	0.9 m x 0.9 m	Black	9.95
<del>SS010006</del>	<del>0.9 m x 0.9 m (14 mm)</del>	<del>Black</del>	

## Technical Specifications

<b>Material</b>	Rubber mix, including >50% recycled material
<b>Surface Finish</b>	Textured with holes to allow drainage
<b>Product Height</b>	18 mm
<b>Hole Size</b>	22 mm
<b>Min. Operating Temperature</b>	-20°C
<b>Max. Operating Temperature</b>	+130°C
<b>Resistance to Chemicals</b>	Natural rubber offers limited resistance to chemicals and oils
<b>Notes</b>	Silicone is used in the production process of the mats and a residue will possibly be left on the mat. This can be washed off using hot soapy water.
<b>Slip Tested to</b>	DIN 51130 - R10

<b>Environmental Resistance</b>	Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.
<b>UV Resistance</b>	Yes
<b>Typical Applications</b>	All industrial environments, Bars, Catering environments, Areas where swarf is prevalent. Children's play areas.
<b>Installation Method</b>	Loose lay interlocking tiles
<b>Accessories</b>	Bevelled corner edges
<b>Cleaning Method</b>	Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt
<b>COO (Country of Origin)</b>	IN
<b>Storage and application</b>	Store at room temperature, free from deformations.
<b>Tensile Strength</b>	3 to 3.5 MPa

