



K-Mat

Reduce fatigue and slips on greasy floors



- Contains nitrile to offer the best resistance to oils and chemicals.
- Ideal for food processing and manufacturing locations due to its excellent resistance to grease, fats and detergents.
- Easily cleaned in a commercial washing machine.
- Raised pattern surface for exceptional slip-resistance (tested to DIN 51130).
- Open holes efficiently drain liquids and capture debris.
- Hygienic anti-microbial properties make it suitable for food processing locations.

Parts

Part Number	Size	Colour	Weight (kg)
KM010001	0.92 m x 1.53 m	Black	7.5
KM010002	0.92 m x 2.9 m	Black	10

Technical Specifications

Material	NBR
Surface Finish	Cross-grip
Product Height	9 mm
Product Weight	7.75 kg
Hole Size	12.5 mm
Min. Operating Temperature	0°C
Max. Operating Temperature	+100°C
Resistance to Chemicals	Resistant to oil
Environmental	Suitable for kitchens and oily indoor environments
Manufacturing process	Compression moulding

Resistance

UV Resistance Yes

Typical Applications Food manufacturing, Kitchens, General industrial, Machine tool areas where swarf is prevalent

Installation Method Loose lay

Cleaning Method Pressure hose

COO (Country of Origin) LK

Tensile Strength 5 MPa

Elongation 400%

Application Temperature -30°C to 90°C

Slip Tested to DIN 51130 - R11

