




Premier Track Protect internal flooring with heavyduty, premium quality entrance tiles



- Effectively removes moisture and debris, even from wheeled trolleys, without buckling.
- Safe for high heeled footwear, heels won't get stuck in the tiles.
- Move, clean or replace individual tiles they clip together with ease.
- Easily cut to shape, so you can fit to any space and install faster with fewer specialist tools.
- Exceptionally durable carpet inserts manufactured from ECONYL®, a recycled nylon material made from discarded fishing nets and other sources.
- · Ideal for recessed entrance wells.
- Fire tested to BS EN 13501-1 and slip tested to BS 7976-2.













Anthracite Open Construction



Grey Open Construction



Anthracite Closed Construction

see a see a second second

Grey Closed Construction

Parts

Part Number	Size	Colour	Weight (kg)
PT010101	29 cm x 44 cm	Anthracite	1.2
PT010101C	30 cm x 45 cm	Anthracite	1.2
PT010601	29 cm x 44 cm	Grey	1.1
PT010601C	30 cm x 45 cm	Grey	1.1

Technical Specifications

Material	ECONYL® Regenerated Nylon in PVC tile		
Product Height	13.5 mm		
Typical Applications	Entrance areas		
Installation Method	Installed in to recessed well		
Fire Tested	BS EN 13501-1 Class Cfl - s2		
COO (Country of Origin)	UK		
Guarantee	5 years		
Notes	Alba is a tufted carpet product and therefore its appearance can vary depending on the direction of the pile and the light in the surrounding environment. To achieve a uniform appearance consider hoovering the product in a single direction.		
Slip Tested to	BS 7976-2 - low slip potential		
Tile height	12.5 mm		

Industroclean (Pty) Ltd +27 (0) 11 801 4600 Corner Picaroon & Raft Street, Laser Park, Honeydew, 2170

info@industroclean.co.za www.industroclean.co.za