

envirowork mk

SAFETY DATA SHEET

According to ISO 11014

Original prep date: 14-02-2023

Last revision date: 19-08-2026



Section 1: Chemical product and company information

Trade name:	Envirobowl MK
Product details:	Toilet bowl cleaner & decalcifier
Recommended uses:	For decalcification of acid resistant surfaces.
Manufacturer:	Industroclean (Pty) Ltd Unit 302, Malibongwe Industrial Park Cnr R114 & Malibongwe Drive Nooitgedacht 1739
Emergency telephone number:	+27 11 801 4600

Section 2: Hazards identification

ATE _{mix} classification	Not classified
Corrosive to metals	Category 1: H290
Skin irritation	Category 2: H315
Serious eye damage	Category 2: H319

Signal word: Danger

Hazard symbols:



Hazard statements:

H290 – May be corrosive to metals.

H303 – May be harmful if swallowed.

H315 – Causes skin irritation.

H319 – Causes serious eye irritation.

Precautionary statements:

P260 – Do not breathe dust/fume/gas/mist/vapours/spray.

P264+P265 – Wash hands thoroughly after handling and do not touch eyes.

P265 – Do not touch eyes.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

Section 3: Composition / Information on hazardous ingredients

Description: Mixture

Hazardous components $\geq$ cut-off level: None

Section 4: First aid measures

P304 IF INHALED: Remove to fresh air. P317 Get medical help.

P302 IF ON SKIN: P354 Immediately rinse with water for several minutes. P361 Take off immediately all contaminated clothing. P363 Wash contaminated clothing before reuse.

P305 IF IN EYES: P354 Immediately rinse with water for several minutes. Immediately transport the patient to the eye doctor / hospital. Continue rinsing during transport with isotonic saline solution or water. P338 Remove contact lenses, if present and easy to do. Continue rinsing.

P301 IF SWALLOWED: P330 Rinse mouth. P331 Do not induce vomiting. During spontaneous vomiting hold the patients head low with the body in a prone position to avoid aspiration. P316 Get medical help immediately.

Section 5: Fire-fighting measures

Suitable extinguishing agents: Water spray jet, extinguishing powder, CO₂, foam.

Unsuitable extinguishing agents: None.

Specific hazards: Not determined.

Special protective equipment: Wear self-contained breathing apparatus and special tightly sealed suit.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures: Particular danger of slipping on leaked/spilled product. Wear protective clothing (See section 8). Keep unprotected persons away. When selecting the protective suit, attention has to be paid to the complete and safe protection of skin and mucous membranes. Impermeable protective clothes, protective boots must be made of neoprene, complete face protection and nitrile-rubber gloves with long tops should be worn.

Environmental precautions: P390 Absorb spillage to prevent material-damage. Prevent from spreading (e.g. by enclosing with a ring of chemical absorbent). Inform authorities in case of contamination of water or sewage system.

Methods and material for containment and cleaning up: Collect large amounts in suitable container. Cover the rest with absorbent, mix intensively and collect mechanically.

Section 7: Handling and storage

Precautions for safe handling: Provide good room ventilation or local exhaust ventilation at the workplace. Product to be diluted with cold water to prevent bacterial growth.

Requirements to be met by storerooms and containers: P405 Store locked up. Ensure sufficient ventilation. Store only in the original container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Fill only into labelled containers and do not leave the container open.

Section 8: Exposure controls and personal protection

Occupational exposure limit values: None

Engineering controls: Not applicable

Personal Protective Equipment:

Use safety goggles.



Wear safety gloves.

Section 9: Physical and chemical properties

Description	Result
Appearance	Liquid
Colour	Red
Odour	Citrus fresh
Melting / Freezing range	Not determined
Boiling point / Boiling range	> 100°C
Flash point	Not applicable
Self-inflammability	Not applicable
Danger of explosion	Not applicable
Density at 20°C	1.070 g/cm ³
Miscibility with water	Completely miscible
pH value concentrate at 20°C	1.0 ± 0.5
Volatile organic compound (Conc %)	0.4%



Fluoro-compounds (Conc %)	0%
---------------------------	----

Section 10: Stability and reactivity

Chemical stability: No decomposition up to the boiling point. Under recommended storage conditions, this product is stable for up to 3 years.

Reactions: No dangerous reactions known.

Incompatible materials: None

Section 11: Toxicological information

Acute oral toxicity estimate: >5000

Germ cell mutagenicity: Classification criteria are not met.

Carcinogenicity: Classification criteria are not met.

Reproductive toxicity: Classification criteria are not met.

Section 12: Ecological information

Bioaccumulation potential: No significant accumulation in organisms is expected as a result of the distribution coefficient of n-octanol/water (log Pow).

Results of PBT and vPvB assessment: The product does not contain a substance fulfilling the PBT criteria or the vPvB criteria.

Adverse effects: The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Mobility in soil: The product will not evaporate into the atmosphere from the water surface and adsorption to solid soil phase is not expected.

Biodegradability: Readily biodegradable (according to OECD criteria).

Section 13: Disposal considerations

This product can be safely disposed according to the local municipal, provincial or national regulations. Dispose of packaging in an approved receptacle or incinerator.

Section 14: Transport information

UN number: UN 1760

UN proper shipping name: CORROSIVE LIQUID, N.O.S.

Transport hazard class(es): Class 8 — Corrosive substances



Packing group: III

Environmental hazards: Marine pollutant (IMDG): Yes. Environmentally hazardous substance (UN 3077 / UN 3082): Not applicable — the corrosive hazard determines the classification.

Special precautions for user: Transport only in closed, UN-approved packagings that are correctly marked and labelled (SANS 10229-1). Secure packages upright against movement and protect from mechanical damage. Do not load with foodstuffs, feedstuffs or pharmaceuticals. Where the consignment exceeds the exempt quantity the vehicle shall carry the transport emergency card and emergency response information required by SANS 10232-1/-3/-4 and the equipment required by SANS 10231, and the driver shall hold a valid professional driving permit endorsed for dangerous goods.

Transport in bulk according to IMO instruments: Not applicable. The product is not carried in bulk under Annex II of MARPOL or the IBC Code.

Road transport – South Africa: National Road Traffic Act 93 of 1996, Chapter VIII of the National Road Traffic Regulations (Transportation of Dangerous Goods, Regs 273–283B), read with:

- **SANS 10228 (identification and classification of dangerous goods):** UN 1903, Class 8, Packing Group III.
- **ADR (as adopted in South Africa):** classification code C9; hazard identification (Kemler) number 80; tunnel restriction code (E); transport category 3 – full operational requirements apply above 1 000 l total dangerous goods per transport unit (ADR 1.1.3.6 / SANS 10231); limited quantities (ADR Chapter 3.4): 5 l per inner packaging.
- **Packaging:** UN-certified packagings per SANS 10229-1; intermediate bulk containers (IBCs) per SANS 10233.
- **Placarding / emergency information system:** SANS 10232-1; emergency action code (SANS 10232-3): 2X.
- **Transport emergency card (Tremcard):** per SANS 10232-4 – must be carried in the vehicle cab and be accessible to the driver.
- **Operational requirements (SANS 10231):** dangerous goods declaration by the consignor; driver to hold a valid professional driving permit with dangerous goods endorsement (PrDP category D); prescribed vehicle equipment, placarding, incident procedures and route/parking requirements.

Sea transport – IMDG Code (Merchant Shipping Act 57 of 1951, administered by SAMSA):

- UN 1760, Class 8, Packing Group III; EmS: F-A, S-B; marine pollutant: Yes. Stowage and segregation per the IMDG Code for Class 8.

Air transport – ICAO Technical Instructions / IATA Dangerous Goods Regulations (Civil Aviation Regulations, Part 92):

- UN 1760, Class 8, Packing Group III; packing instructions and quantity limits per the current IATA DGR.

Other:

- WCO HS code / tariff code: 3402.90
- Emergency response guide (ERG): Guide 154

Section 15: Regulatory information

- Eco-choice licence number: ECP20230301-1
- Occupational Health and Safety Act 85 of 1993
- Regulations for Hazardous Chemical Agents, 2021
- Identification and Classification of Dangerous Goods for Transport
- Relevant SABS South African National Standards and Specific Permit Conditions
- Waste Classification and Management Regulations
- Metropolitan Municipal Services and Waste Management By-Laws
- Globally Harmonized System of Classification and Labelling of Chemicals (GHS)
- Safety Data Sheets for Chemical Products, SANS11014
- Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung: GESTIS Substance Database
- European Chemicals Agency: Echa Chem
- Department of Employment & Labour (Competent Authority for SDS's in SA)
- OECD 301 Ready Biodegradability

Section 16: Other information

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks pertaining to the use of the product are therefore assumed by the user and we expressly disclaim all warranties of every kind and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use of suitability of the product. Appropriate warning and safe handling procedures should be provided to handlers and users.

Data sheet prepared by: Valiant Compliance Solutions (Pty) Ltd